



OLON[®]

**IT ALL COMES
TOGETHER**

LINK25 FORMABLE LAMINATE



Olon's LINK25 Formable Laminate is postformable for edges, tops or corners.

Available in perfect colour matches to TFL and HPL, it is ideal for refacing or new installations and is recommended for vertical or light duty horizontal surfaces.

LINK25 is NEXGEN[®] certified and complements the full product selection of kitchen door components, accessory mouldings, and edgebanding available from Olon.

LINK25 FORMABLE LAMINATE

NEXGEN[®]
Laminates

Olon NEXGEN[®] LINK25 Formable Laminate is intended for application to vertical or light duty horizontal surfaces where design, appearance, quality, durability and outstanding resistance to impact, scuff, stain, wear and heat resistance are required.

NOTABLE FEATURES

- Exact match to over 200 TFL (melamine) colours
- High heat and scratch resistance
- Colour remains consistent year after year
- Antimicrobial protection is built into the manufacturing process
- Postformable
- Cuts easily with sheers, straight edge knife or scissors
- Bondable with most conventional adhesives
- Great for onsite resurfacing or new installations
- Performance measured by NEMA LD3-2005

For more technical information, please go to the downloads section of www.olon.com

PRODUCT OFFERING

Olon NEXGEN[®] Certified LINK25 Formable Laminate is a visually preferable laminate with a high degree of colour clarity and rich authentic textures.

- Stock colours available in 4' x 9' sheets (8 sheet minimum)
- Custom colours or sheet lengths (2000 sq ft)
- Continuous rolls (roll of 4' x 500')

CATEGORY	STANDARD	TYPICAL VALUES
Wear	NEMA LD3-2005	Solid: 400 Cycles Print: 170 Cycles
Stain	NEMA LD3-2005	1-14 No effect 15 Slight
Cleanability	NEMA LD3-2005	No effect
Light Resistance	NEMA LD3-2005	Slight
High Temperature	NEMA LD3-2005	Slight
Radiant Heat	NEMA LD3-2005	No effect
Boiling Water	NEMA LD3-2005	No effect
Impact	NEMA LD3-2005	24"



GEORGETOWN, ON
Tel: (800) 387-2319
Fax: (905) 877-7383

JEFFERSONVILLE, IN
Tel: (812) 256-6400
Fax: (812) 256-6450